

## OPERATION INSTRUCTIONS



- 1 PLACE YOUR SAFEAIR ULTRA AIR PURIFIER UNIT ON A STURDY SURFACE & INSTALL THE POWER ADAPTER. FOR BEST RESULTS & COVERAGE, POSITION THE UNIT IN AN OVERHEAD LOCATION OR AT LEAST 5 FEET FROM THE FLOOR.
- 2 PRESS THE POWER BUTTON TO TURN ON THE UNIT.
- 3 USE THE FAN SPEED CONTROL BUTTONS TO ADJUST THE FAN OUTPUT TO YOUR PREFERENCE. THE FAN OUTPUT SPEED CAN BE FOUND ON THE LED DISPLAY SCREEN.
- 4 USE THE MODE/COVERAGE CONTROL BUTTONS TO ADJUST THE OZONE OUTPUT LEVEL AS NEEDED FOR THE ROOM OR SPACE UP TO 3000 SQ. FEET.
- 5 TO ACTIVATE \*PCO ONLY MODE\*, ADJUST THE MODE/COVERAGE TO THE LOWEST POSSIBLE SETTING. WHEN ACTIVATED, THE LED SCREEN WILL DISPLAY "PCO NORMAL."
- 6 TO ACTIVATE \*ULTRA PURIFYING MODE\*, PRESS THE AWAY MODE BUTTON TO SELECT 30, 60 OR 120 MINUTES. THIS WILL ACTIVATE A BOOST OF OZONE CONCENTRATION FOR EXTREME ODOR REMOVAL & IS RECOMMENDED TO USE AT YOUR DISCRETION.

## THETECHNOLOGY

# SAFEAIR ULTRA IS POWERED BY 4 PROVEN PURIFYING METHODS TO TRANSFORM YOUR INDOOR AIR:

#### ELECTROSTATIC FILTRATION




CAPTURES LARGE PARTICLES SUCH AS HAIR, DIRT & DUST.

## ACTIVATED OXYGEN



GENERATES OZONE MOLECULES TO REMOVE SMOKE & ODORS.

### PHOTOCATALYTIC OXIDATION



USED BY NASA TO DESTROY AIRBORNE BACTERIA & GERMS.

### NEGATIVE IONIZATION



HELPS CREATE A
NATURAL CLEAN &
FRESH AIR FEELING.

# CLEANING & MAINTENANCE

- 1 UNPLUG UNIT & REMOVE THE BACK COVER PANEL TO ACCESS INTERNAL COMPONENTS TO PERFORM CLEANING. LOCATE THE SCREW ON THE BACK OF THE UNIT & USE A STANDARD PHILLIPS SCREWDRIVER TO REMOVE THE COVER.
- 2 TO CLEAN THE ELECTROSTATIC FILTER, REMOVE THE HONEYCOMB FILTER SCREEN & DISCARD CAPTURED HAIR OR DUST PARTICLES. YOU MAY ALSO USE A VACUUM CLEANER OR COMPRESSED AIR TO GENTLY REMOVE PARTICLES FROM THIS FILTER.
- 3 TO CLEAN THE CERAMIC OZONE PLATE, CAREFULLY SLIDE THE PLATE OUT OF THE UNIT & SCRUB WITH WARM SOAPY WATER. ALLOW CERAMIC PLATES TO DRY COMPLETELY BEFORE RE-INSTALLING.
- 4 AFTER CLEANING & REASSEMBLING UNIT, PRESS "MAINTENANCE RESET" ON THE FRONT CONTROL PANEL TO RESET YOUR UNIT BEFORE USE.
- 5 WHEN THE PCO CELL HAS DEPLEATED, CAREFULLY REMOVE THE PCO CELL COMPONENT FROM THE UNIT UNTIL A REPLACEMENT IS READY FOR INSTALL.

# **CUSTOMER SUPPORT**

FOR QUESTIONS OR OPERATIONAL CONCERNS ABOUT YOUR AIR PURIFIER PRODUCT, PLEASE CONTACT OUR SERVICE TEAM AT 800-599-5191 OR VISIT OUR WEBSITE AT WWW.ECOINVENTIONS.COM